

	ENGLISH	SI	
Performance			
Measurement Range(for ±5V output)	1 psi	6.89 kPa	
Sensitivity(± 15 %)	5000 mV/psi	725 mV/kPa	
Maximum Pressure(Dynamic)	10 psi	68.9 kPa	
Maximum Pressure(static)	50 psi	345 kPa	
Resolution	0.02 mpsi	.00013 kPa	
Resonant Frequency	≥ 40 kHz	≥ 40 kHz	
Rise Time(Reflected)	≤ 12.5 μ sec	≤ 12.5 μ sec	
Low Frequency Response(-5 %)	2.5 Hz	2.5 Hz	
Non-Linearity	≤ 1 % FS	≤ 1 % FS	[1]
Environmental			
Acceleration Sensitivity	≤ 0.002 psi/g	≤ 0.0014 kPa/(m/s ²)	
Temperature Range(Operating)	-65 to +250 °F	-54 to +121 °C	
Temperature Coefficient of Sensitivity	≤ 0.03 %/°F	≤ 0.054 %/°C	
Maximum Shock	1000 g pk	9807 m/s ² pk	
Electrical			
Output Polarity(Positive Pressure)	Positive	Positive	
Discharge Time Constant(at room temp)	≥ 0.2 sec	≥ 0.2 sec	
Excitation Voltage	24 to 27 VDC	24 to 27 VDC	
Constant Current Excitation	2 to 20 mA	2 to 20 mA	
Output Impedance	<100 ohm	<100 ohm	
Output Bias Voltage	7 to 14 VDC	7 to 14 VDC	
Physical			
Sensing Geometry	Compression	Compression	
Sensing Element	Quartz	Quartz	
Housing Material	17-4 Stainless Steel	17-4 Stainless Steel	
Diaphragm	316L Stainless Steel	316L Stainless Steel	
Sealing	Welded Hermetic	Welded Hermetic	
Electrical Connector	10-32 Coaxial Jack	10-32 Coaxial Jack	
Weight	1.2 oz	35 gm	

OPTIONAL VERSIONS		
Optional versions have identical specifications and accessories as listed for the standard model except where noted below. More than one option may be used.		
E - Emralon coating		
Coating	Emralon	Emralon
Electrical Isolation	10 ⁸ ohm	10 ⁸ ohm
J - Ground Isolated		[3]
N - Negative Output Polarity		
W - Water Resistant Cable		[4]
Supplied Accessory : Model 060A11 Delrin clamp nut 3/4-16-2A thd 3/4" hex (1)		
WM - Water Resistant Cable		[4]
Supplied Accessory : Model 060A13 Metric Delrin clamp nut M20 x 1.5-6g thd 20 mm hex (1)		

NOTES:
 [1] Zero-based, least-squares, straight line method.
 [2] See PCB Declaration of Conformance PS023 for details.
 [3] Used with optional mounting adaptor.
 [4] Clamp nut installed prior to cable attachment

SUPPLIED ACCESSORIES:
 Model 060A11 Delrin clamp nut 3/4-16-2A thd 3/4" hex (1)
 Model 060A13 Metric Delrin clamp nut M20 x 1.5-6g thd 20 mm hex (1)
 Model 065A36 Seal, .687" OD x .625" ID x .060", Delrin (3)

Entered: <i>OMW</i>	Engineer: <i>NIL</i>	Sales: <i>KWJ</i>	Approved: <i>EB</i>	Spec Number:
Date: <i>8/24/10</i>	Date: <i>8/24/10</i>	Date: <i>8/24/10</i>	Date: <i>8/24/10</i>	22933



All specifications are at room temperature unless otherwise specified.
 In the interest of constant product improvement, we reserve the right to change specifications without notice.
 ICP® is a registered trademark of PCB Group, Inc.

PCB PIEZOTRONICS
PRESSURE DIVISION

3425 Walden Avenue, Depew, NY 14043

Phone: 716-684-0001
 Fax: 716-686-9129
 E-Mail: pressure@pcb.com